



RECOMMENDED P.C.B LAYOUT

Specifications

Current Rating: 2Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 500V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 NYLON-6T

ROHS COMPLIANT

Ordering Information

HFLSSVX2	-	XX	XX	XXX	T	P	X
No. of Pins Per Row	Standard Plating	Pin Length	Material	Post	Post	Post	Packaging
04-40	01=Gold Flash 02=Gold 30" 11=11in	001=6.5 XXX=Select W	L=ICP T=6T	P=With Post W=Without Post			TR=Trape-tell T=Tube
	XX=Select Plating						

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	ELETE TECHNOLOGY., CO LTD 億潔得股份有限公司
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X. ±5° .X ±2° .XX ±1° .XXX ±0.5°	Andy2005.08.12		
UNIT:mm	SCALE 1:1	CHECK	DATE	FILE NAME (品名)
A4	SHEET: 1 of 1	APPRO.	DATE	PART NO (料号)
				DRAWING NO.(图号)
				REV/AD