


Specifications
 Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 For 02~24pins, use the plastic of PBT,
 while 25~40pins using Nylon6T +20%
 recycle plastic

ROHS COMPLIANT

Recommended P.C.Board
 Hole Layout



Ordering Information

Ordering Information

HFNSR2 - XX XX XXX P
 No. of Pins Standard Plating Pin Length Material
 Per Row 01=Gold Flash 001=2.8 L=CP
 02=Gold 30μ 002=2.8 T=ML6T
 11=TiN XXX=Select A P=PBT
 X=Select Plating

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X°. ±5' .X° ±2' .XX° ±1' .XXX° ±0.5'	Andy2005.08.12	
UNIT:mm	SCALE 1:1	APPRO.	DATE
A4	SHEET: 1 of 1		
FILE NAME (品名)		ELEETE TECHNOLOGY CO., LTD	
PART NO (料号)		億濠得股份有限公司	
DRAWING NO.(图号)		HFNSR2-XXXXXXXP	
		2.54MM Female Header R/A TYPE	
		HFNSR2-01	
		REV:A0	