


**Specifications**  
 Current Rating: 3Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 600V AC/DC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C

**Materials**  
 Contact Material: Phosphor Bronze  
 Insulation Material: Polyester, UL 94V-0  
 P.B.T

**ROHS COMPLIANT**

Recommended P.C.Board  
 Hole Layout



**Ordering Information**

HFNSS5U - XX XX XXX P  
 No. of Pins Standard Plating Pin Length Material  
 Per Row 01=Gold Flash 001 =3.0 L=CP  
 02=Gold 30" XXX=Select A T=MLGT  
 11=Fin P=PPt  
 X=Select Plating

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	FILE NAME (品名)	PART NO (料号)	DRAWING NO.(图号)	REV/AO
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X°. ±5' .X° ±2' .XX° ±1' .XXX° ±0.5'	Andy2005.08.12					
UNIT:mm	SCALE 1:1	APPRO.	DATE	ELEETE TECHNOLOGY CO., LTD 億潔得股份有限公司			
A4	SHEET: 1 of 1			Female Header DIP TYPE			