


Specifications
 Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 1.) 02~24PIN 塑膠材質用 P.B. 料生產.
 2.) 25~40PIN 塑膠材質用 PA6T+20% 料生產.

ROHS COMPLIANT

Recommended P.C.Board
 Hole Layout



Ordering Information

HFNSR3 - XX XX XXX P
 No. of Pins Standard Plating
 Per Row 01=Gold Flash Pin Length
 02=Gold 3U" 001=3, 2/1.8
 11=Tin XXX=Select A/R
 X=Select Plating Material
 L=LCP
 T=ML6T
 P=PB1

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X°. ±5° X° ±2° XX° ±1° XXX° ±0.5°	Andy2005.08.12	
UNIT:mm	SCALE 1:1	APPRO.	DATE
A4	SHEET: 1 of 1		
FILE NAME (品名)		ELEETE TECHNOLOGY CO., LTD	
PART NO (料号)		億溙得股份有限公司	
DRAWING NO.(图号)		HFNSR3-XXXXXXXP	
REV/AO		HFISR3-01	