

Specifications

Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials


Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0

注: 02~24PIN塑膠材料實用P.B.材料生產,
 25~40PIN塑膠材料實用PA6T+20%料生產.

ROHS COMPLIANT

Recommended P.C.Board

Hole Layout



Ordering Information

HFNSR5 - XX XX XXX P
 No. of Pins Standard Plating
 Per Row 01=Gold Flash 001=3,2/1.6
 02=Gold 30μ XXX=Select A/R
 11=Pin
 X=Select Plating
 Material
 L=CP
 T=ML6T
 P=PBT

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X. ±5° .X ±2° .XX ±1° .XXX ±0.5°	Andy/2005.08.12	
UNIT:mm	SCALE 1:1	APPRO.	DATE
A4	SHEET: 1 of 1		
FILE NAME (品名)		ELEETE TECHNOLOGY CO., LTD	
PART NO (料号)		億潔得股份有限公司	
DRAWING NO.(图号)		HFNSR5-XXXXXXXP	
		HFISR5-01	
		REV:A0	