



Recommended P.C. Board

Hole Layout

ROHS COMPLIANT

注: 02~24PIN塑膠材質用P.B.T料生產,
25~40PIN塑膠材質用PA6T+20%料生產.

Specifications
 Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials
 Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0

Ordering Information

HFNSS9 - XX XX XXX P
 No. of Pins Standard Plating Pin Length Material
 Per Row 01=Gold Flash 001=3.0 L=CP
 02=Gold 3U" 02=Gold 3U" T=MG
 11=Pin 11=Pin P=PP
 X=Select Plating XXX=Select A

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	FILE NAME (品名)
X. ± .X ±0.38 .XX ±0.25 .XXX ±0.13	X. ±5° .X ±2° .XX ±1° .XXX ±0.5°	Andy2005.08.12	2.54MM Female Header DIP TYPE
UNIT:mm	SCALE 1:1	APPRO. DATE	PART NO (料号)
A4	SHEET: 1 of 1		HFNSS9-XXXXXXXXXP
			DRAWING NO.(图号)
			HFISS9-01
			REV:AO

ELEETE TECHNOLOGY CO., LTD
 億潔得股份有限公司